

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : <b>G06F 15/16, 12/00, 19/00</b>	A1	(11) International Publication Number: <b>WO 99/27462</b> (43) International Publication Date: <b>3 June 1999 (03.06.99)</b>
<p>(21) International Application Number: <b>PCT/US98/24055</b></p> <p>(22) International Filing Date: <b>12 November 1998 (12.11.98)</b></p> <p>(30) Priority Data: 08/975,749                    20 November 1997 (20.11.97) US</p> <p>(71) Applicant: CYBERSTAR, L.P. [US/US]; 1965 Charleston Road, Mountain View, CA 94043 (US).</p> <p>(72) Inventors: OLLIKAINEN, Ari; 544 Alger Drive, Palo Alto, CA 94306 (US). KERO, Terrence, E., F.; 710 Talbot Avenue, Pacifica, CA 94044 (US).</p> <p>(74) Agent: GREEN, Clarence, A.; Perman &amp; Green, LLP, 425 Post Road, Fairfield, CT 06430 (US).</p> <p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p>		

Published

*With international search report.*

(54) Title: MODULAR DIGITAL DATA COMMUNICATION CYBERSTATION AND CYBERSERVER



(57) Abstract

A broadcast and interactive data distribution system that distributes broadcast and interactive data transmitted by way of a geostationary satellite (11), and optionally by way of a cable system (16), to personal computers (35). The system comprises a modular digital data communication cyberstation (20) that is a modular computer and server that is external to the personal computers (35) to which data is to be distributed. The cyberstation (20) receives, optionally stores, and distributes the broadcast and interactive data to the personal computers (35). The cyberstation (20) has wireless (28) and optional wired interfaces (29) for communicating with the personal computers (35). An optional cable modem (26) may be used to directly communicate with the cable system (16). A satellite receiver (21) is employed to communicate with the geostationary satellite (11), and a low-earth-orbit satellite transceiver (27) is employed to communicate with low-earth-orbit satellites (12) used to support information requests, data billing and status/diagnostic reporting to a service provider. An optional pass-through television interface (33) may be used to display the broadcast data on a television receiver (37). The data distribution system and cyberstation (20) thus provide for high-speed Internet access and web content and large file download delivery to personal computers (35) of consumers and businesses by way of satellite and other systems.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KR	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		

**MODULAR DIGITAL DATA COMMUNICATION  
CYBERSTATION AND CYBERSERVER**

**BACKGROUND**

The present invention relates generally to broadcast and interactive data distribution systems, and more particularly, to a broadcast and interactive data distribution system for distributing broadcast and interactive data services to personal computers using a modular computer/server that is external to the personal computers.

The majority of conventional systems that deliver broadcast and interactive data to personal computers have used modems that are directly connected to the personal computers. A modems interconnects a personal computer by way of telephone lines to another computer such as one provided by an Internet service provider, for example, that is connected to the Internet, and over which broadcast and interactive data is sent to the personal computer. In order for the personal computer to receive data, it and the modem must me turned on.

Another data distribution system uses a conventional modem directly connected to a personal computer to transmit requests for data over the Internet and the requested data is returned by way of a satellite link that transmits the data to a processing card installed in the personal computer. This system transmits the requested data at relatively high speed (400 MHz data transfer rate), which is on the order of from ten to twenty times the speed of typical modems. As with the conventional modem-based system, in order for the personal computer to receive data, it and the modem must me turned on.

Accordingly, it is an objective of the present invention to provide for an improved data distribution system that distributes broadcast and interactive data services to personal computers and that overcomes limitations of prior art systems.

5

## SUMMARY OF THE INVENTION

To accomplish the above and other objectives, the present invention is a broadcast and interactive data distribution system that comprises a modular digital data communication cyberstation for distributing broadcast and interactive data services to personal computers. The cyberstation provides for a flexible interface between 10 satellite/wireless broadcast/two-way interactive data services and personal computers that may be configured to suit a variety of different communications alternatives and deployment situations. An enhanced version of the cyberstation is known a cyberserver which includes additional memory and data storage capability.

In contrast to conventional systems, the cyberstation is a modular standalone 15 data receiving and sending computer and server that is external to the personal computers to which data is to be distributed. The cyberstation of the data distribution system receives, optionally stores, and distributes the broadcast and interactive data to the personal computers. The cyberstation thus receives broadcast data transmissions and forwards or stores them on behalf of the personal computers. The cyberstation is 20 preferably used to wirelessly interconnect personal computers to satellite networks. The cyberstation thus acts as an interface to satellite/wireless data networks on behalf of client personal computers.

The cyberstation includes subsystems for receiving and storing broadcast data 25 continuously (24 hours per day, 7 days per week) without requiring the personal computers that are to ultimately receive the data to be turned on. Furthermore, the cyberstation includes subsystems that permit it to communicate with the personal computers using wireless or optional wired connections.

The cyberstation is configured in a set-top-box form factor and supports a 30 variety of high-speed interfaces, including geosynchronous satellite receiver and transmitter interfaces, a wireless local area network (LAN) interface, and a low earth orbit low-bandwidth satellite transceiver interface (modem). The modular digital data communication cyberstation may also include a cable modem, a pass-through television interface, a wired local area network interface, a wireless terrestrial data service transceiver, and a smart card circuit.

35 The cyberstation thus provides high-speed Internet access and web content and large file download delivery to personal computers of consumers and businesses by way of satellite and other wireless systems. The cyberstation preferably delivers these

services in the form of a reliable, always-on, wireless digital interface to the personal computers. The cyberstation thus provides a means for implementing a variety of customized stand-alone receiver-transmitter stations that can provide service to multiple household or business personal computers using wireless or optional wire local area networks as a local communication system.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

The various features and advantages of the present invention may be more readily understood with reference to the following detailed description taken in conjunction with the accompanying drawing figure which illustrates a broadcast and interactive data distribution system employing a modular digital data communication cyberstation in accordance with the principles of the present invention.

10

#### DETAILED DESCRIPTION

15

Referring to the sole drawing figure, it illustrates the architecture of a broadcast and interactive data distribution system 10 employing a modular digital data communication cyberstation 20 in accordance with the principles of the present invention. The broadcast and interactive data distribution system 10 comprises a geostationary earth orbiting (GEO) satellite 11, and a constellation of low earth orbit (LEO) satellites 12, and optionally includes a cable system 16. The geostationary earth orbiting satellite 11 orbits the earth at 22,300 nautical miles in synchronous orbit. The constellation of low earth orbit satellites 12 orbit the earth at about 600 nautical miles in synchronous orbit. The constellation of low earth orbit satellites 12 may be those of the Globalstar system developed by the assignee of the present invention. The optional cable system 16 has an antenna 17 for receiving broadcast data transmitted by way of the geostationary earth orbiting satellite 11 and cabling 18 that interconnects the cable system 16 to residences and businesses that it serves.

20

The cyberstation 20 employs several antennas for communication purposes. A first antenna 13 for communicating with the geostationary earth orbiting satellite 11.

25

The first antenna 13 is a small diameter dish antenna 15. A second antenna 14 is provided for communicating between the ground station 13 and one of the low earth orbit satellites 12. The second antenna 14 is a small whip antenna attached to the first antenna 13. An optional third antenna 15 may be used to communicate with a wireless terrestrial data service. The respective antennas 13, 14, 15 are hardwired to various communication devices of the cyberstation 20, as will be described below. The respective antennas 13, 14, 15 provide wireless communications links between the

35

cyberstation 20 and the geostationary earth orbiting satellite 11, the low earth orbit satellite 12, and the terrestrial data service.

The cyberstation 20 provides a digital interface that distributes broadcast and interactive data derived from the geostationary earth orbiting satellite 11, and optionally 5 from the cable system 16 and the terrestrial data service, to personal computers 35 located in residences and businesses. The cyberstation 20 comprises a variety of subsystems and software that cooperate to distribute the broadcast and interactive data derived from service providers to the personal computers 35. Service providers uplink the broadcast and interactive data by way of the geostationary earth orbiting satellite 11, 10 which data is downlinked to the first antenna 13. The downlinked data is then coupled by way of the hardwired connection to the cyberstation 20. Service providers may also uplink the broadcast and interactive data to the geostationary earth orbiting satellite 11 which data is downlinked to the cable system 16 by way of its antenna 17. The data downlinked to the cable system 16 is then retransmitted by way of the cabling 18 to the 15 cyberstation 20.

The cyberstation 20 comprises a computer processor and software 24 that includes a geostationary (GEO) satellite receiver 21 for communicating by way of the geostationary earth orbiting satellite 11. The geostationary satellite receiver 21 receives broadcast and interactive data from the geostationary earth orbiting satellite 11 by way 20 of the first antenna 13.

A "thin" (i.e., relatively small) operating system (O/S), such as may be provided by the commercially available QNX operating system, for example, and commercially available webserver software 24 are provided that are used to configure and operate the cyberstation 20 and to provide communication services to interface the 25 cyberstation 20 to an Internet service provider. Satellite Internet proxy software 23 interfaces to the operating system and webserver software 24 and is used to control transmission of commands and reception of broadcast and interactive data from the service provider. Internet routing software 25 provides the services of a router to route incoming broadcast and interactive data to the appropriate personal computer 35.

An optional cable modem 26 is provided that is interconnected to the cabling 18 of the cable system 16 to provide a link between the cyberstation 20 and the cable system 16. A low earth orbit (LEO) low-bandwidth (100 bits/second) satellite transceiver 27 (modem) is provided that is used to communicate with the low earth orbit satellites 12 by way of the second antenna 14. The LEO transceiver 27 and antenna 14 30 may also be implemented using a very small aperture satellite (VSAT) transceiver 27, for example, in conjunction with a VSAT antenna to provide higher-speed two-way service. The LEO transceiver 27 and low earth orbit satellites 12 are part of a return 35

path to the service provider that is used to transmit information requests, deliver feed-back, transmit billing data and perform status and diagnostic reporting. Alternatively, a geostationary satellite transmitter 21a may be employed to communicate with the service provider by way of the geostationary earth orbiting satellite 11. Furthermore, the

5. terrestrial transceiver may be used in place of the LEO transceiver 27 and low earth orbit satellites 12 to provide the return path to the service provider, if it is desired.

The cyberstation 20 also comprises a low-cost wireless local area network (LAN) interface 28 having an antenna 28a, and may include an optional wired local area network interface 29. The wireless local area network interface 28 communicates over

- 10 a wireless link (RF or infrared, for example) with personal computers 35 that include a similar wireless local area network interface 28 and antenna 28a. The optional wired local area network interface 29 communicates with personal computers 35 equipped with local area network interface cards 29 by way of a local area network 32, such as an Ethernet network, for example. The optional wired local area network interface 29 is  
15 intended for use in businesses having their own local area networks. Users of the personal computers 35 only need to operate a conventional browser to access the broadcast and interactive data in a manner normally used to access the Internet, E-mail, or on-line services. Thus, the present system 10 is basically transparent to users of the personal computers 35.

- 20 The cyberstation 20 comprises a hard disk 30 that is used to store incoming broadcast and interactive data when personal computers 35 to which the data is to be transmitted are not turned on. The cyberstation 20 can thus receive and store broadcast data continuously (24 hours per day, 7 days per week) without requiring the personal computers 35 that are to ultimately receive the data to be turned on.

- 25 A smart card 31, which is a credit card circuit used in pay-per-view systems, for example, may also be installed in the cyberstation 20. The smart card 31 may be used for billing purposes. A pass-through television (TV) interface 33 may also be installed in the cyberstation 20 which permits television signals to be distributed to a television receiver 37 or to a television receiver card 37 installed in the personal computers 35.

- 30 From the above, it can be seen that the cyberstation 20 provides for a flexible interface between satellite/wireless broadcast/two-way interactive data services distributed using geostationary earth orbiting satellites 11, low earth orbit satellites 12 and/or a cable system 16, and the personal computers 35. The cyberstation 20 may be configured to suit a number of different communications alternatives and deployment situations. An enhanced version of the cyberstation 20 known a cyberserver includes additional computer memory and hard disk 30 storage, but is functionally the same as the cyberstation 20 described above.

One key aspect of the cyberstation 20 is its modularity, in that it can be equipped with a plurality of interface options for satellite reception and transmission, and/or wireless data communication. The cyberstation 20 may be implemented in the form of a computer motherboard having plug-in daughter modules or cards that provide each of 5 the different interfaces described above. Another key aspect of the cyberstation 20 is that it may be configured to provide a wireless interface between a service provider and personal computers 35. Another aspect of the cyberstation 20 is that it may operate at all times, distributing broadcast and interactive data to computers 35 when they are turned on, and storing the data for later distribution to the computers 35 when they are 10 turned off.

Thus, the cyberstation 20 provides a means for implementing a variety of customized standalone receiver/transmitter stations that can provide service to multiple household or business personal computers 35 using wireless or optional wired local area networks 27, 28 as a local communication system. Unlike PC-based satellite 15 receiver cards that must be mated with, draw power from, and be supported by software loaded into the host personal computer, the cyberstation 20 may be set up in a convenient location and left continuously powered up and connected to its antennas 13, 14. The cyberstation 20 provides continuous connectivity to satellite-based data delivery services with a full-time low-bandwidth LEO return path to support information 20 requests, feedback delivery, data billing and status/diagnostic reporting. The terrestrial transceiver 22 and antenna 15 may be used to provide wireless terrestrial data service, where available, to support lower bandwidth Internet access, for example, as an adjunct to high-speed satellite data services.

Thus, an improved data distribution system employing a modular digital data 25 communication that distributes broadcast and interactive data services to personal computers has been disclosed. It is to be understood that the described embodiment is merely illustrative of some of the many specific embodiments that represent applications of the principles of the present invention. Clearly, numerous and other arrangements can be readily devised by those skilled in the art without departing from the 30 scope of the invention.

**CLAIMS**

What is claimed is:

1. A data distribution system for distributing broadcast and interactive data to a personal computer, said system comprising:
    - a geostationary earth orbiting satellite for transmitting broadcast and interactive data derived from a service provider;
    - 5 wireless communication means for transmitting information requests, transmitting billing data and transmitting status and diagnostic data to the service provider;
    - a modular digital data communication cyberstation comprising:
      - operating system and webserver software for configuring and operating
    - 10 the cyberstation and providing communication services to interface the cyberstation to an Internet service provider;
      - satellite Internet proxy software for interfacing to the operating system and webserver software and for controlling transmission of commands and reception of broadcast and interactive data;
    - 15 routing software for routing incoming broadcast and interactive data to the personal computer;
      - a satellite receiver coupled to a first antenna and for receiving broadcast and interactive data by way of the geostationary earth orbiting satellite;
      - a transceiver coupled to a second antenna for communicating by way of
    - 20 the wireless communication means with the service provider;
      - a local area network interface; and
      - a hard disk for storing incoming broadcast and interactive data when the personal computer to which the data is to be transmitted is not turned on;
      - and wherein the personal computer comprises a local area network interface for
    - 25 communicating with the local area network interface of the cyberstation;
      - and wherein the cyberstation distributes broadcast and interactive data received from the geostationary earth orbiting satellite to the personal computer.
2. The system of Claim 1 wherein the wireless communication means comprises one or more low earth orbit satellite.

3. The system of Claim 1 wherein the wireless communication means comprises a terrestrial transceiver for communicating with the service provider.
4. The system of Claim 1 wherein the local area network interfaces of the cyberstation and the personal computer comprise a wireless local area network interface and antenna.
5. The system of Claim 1 wherein the local area network interfaces of the cyberstation and the personal computer comprise a wired local area network interface interconnected by way of a local area network.
6. The system of Claim 5 wherein the local area network comprises an Ethernet network.
7. The system of Claim 3 wherein the local area network interfaces of the cyberstation and the personal computer comprise:
  - a wireless local area network interface and antenna; and
  - a wired local area network interface interconnected by way of a local area network.
8. The system of Claim 1 further comprising:
  - a cable system having an antenna for receiving broadcast and interactive data from the geostationary earth orbiting satellite, and having cabling that interconnects the cable system to the cyberstation; and
  - 5 a cable modem disposed in the cyberstation that is interconnected to the cabling of the cable system to provide a link between the personal computers and the cable system.
9. The system of Claim 1 wherein the cyberstation further comprises a pass-through television interface for distributing television signals to a television receiver for display.
10. The system of Claim 1 wherein the cyberstation further comprises a smart card for billing a customer for services.

11. A data distribution system for distributing broadcast and interactive data to a personal computer, said system comprising:
  - a geostationary earth orbiting satellite for transmitting broadcast and interactive data derived from a service provider;
  - 5 a low earth orbit satellite for transmitting information requests, transmitting billing data and transmitting status and diagnostic data to the service provider;
  - 10 a modular digital data communication cyberstation comprising:
    - operating system and webserver software for configuring and operating the cyberstation and providing communication services to interface the cyberstation to an Internet service provider
    - 15 satellite Internet proxy software for interfacing to the operating system and webserver software and for controlling transmission of commands and reception of broadcast and interactive data;
    - 20 routing software for routing incoming broadcast and interactive data to the personal computer;
    - a satellite receiver coupled to a first antenna and for receiving broadcast and interactive data by way of the geostationary earth orbiting satellite;
    - 25 a low earth orbit transceiver coupled to a second antenna for communicating by way of the low earth orbit satellite with the service provider;
    - and a wireless local area network interface; and
    - a hard disk for storing incoming broadcast and interactive data when the personal computer to which the data is to be transmitted is not turned on;
    - and wherein the personal computer comprises a wireless local area network interface for communicating with the local area network interface of the cyberstation;
    - 25 and wherein the cyberstation distributes broadcast and interactive data received from the geostationary earth orbiting satellite to the personal computer.
12. The system of Claim 11 wherein the cyberstation and the personal computer each further comprise a wired local area network interface interconnected by way of a local area network.
13. The system of Claim 12 wherein the local area network comprises an Ethernet network.


14. The system of Claim 11 further comprising:

a cable system having an antenna for receiving broadcast and interactive data from the geostationary earth orbiting satellite, and having cabling that interconnects the cable system to the cyberstation; and

5 a cable modem disposed in the cyberstation that is interconnected to the cabling of the cable system to provide a link between the personal computers and the cable system.

15. The system of Claim 11 wherein the cyberstation further comprises a pass-through television interface for distributing television signals to a television receiver for display.

16. The system of Claim 12 wherein the cyberstation further comprises a smart card for billing a customer for services.



# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US98/24055

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06F 15/16, 12/00, 19/00

US CL : 370/270, 463; 395/200.48, 200.79, 200.8; 455/2

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 370/270, 463; 395/200.48, 200.79, 200.8; 455/2

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y,E	US 5,758,081 A (AYTAC) 26 May 1998, abstract, fig.1	1-16
Y,E	US 5,852,721 A (DILLON et al.) 22 December 1998, abstract	1-16

Further documents are listed in the continuation of Box C.  See patent family annex.

*A*	Special categories of cited documents:	
"A"	document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"B"	earlier document published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	"A" document member of the same patent family
"P"	document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

11 JANUARY 1999

Date of mailing of the international search report

11 MAR 1999

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

DUNG DINH

Telephone No. (703) 305-9600